
REVIEW OF INVERSION TECHNIQUES FOR SPACEBORNE LIDAR SYSTEMS(U) OPTIMETRICS INC BURLINGTON MAD N GALLON ET AL DEC 86 OMI-181 AFGL-TR-86-0266 F19628-85-C-0178 F/G 20/6 AD-8184 164 1/1 UNCLASSIFIED NL



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

OTIC FILE COPY

AFGL-TR-86-0266

Review of Inversion Techniques for Spaceborne Lidar Systems

Derek W. Gallon John R. Hummel

OptiMetrics, Inc 121 Middlesex Turnpike Burlington, MA 01803



December 1986

Scientific Report No. 2

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

AIR FORCE GEOPHYSICS LABORATORY AIR FORCE SYSTEMS COMMAND UNITED STATES AIR FORCE HANSCOM AIR FORCE BASE, MASSACHUSETTS 01731 "This technical report has been reviewed and is approved for publication"

(Signature)

ERIC P. SHETTLE Contract Manager

Signature)

GEORGE G. KOENIG, Lt Col, USAF

Acting Branch Chief

FOR THE COMMANDER

(Signature)
R. EARL GOOD

Division Director

This report has been reviewed by the ESD Public Affairs Office (PA) and is releasable to the National Technical Information Service (NTIS).

Qualified requestors may obtain additional copies from the Defense Technical Information Center. All others should apply to the National Technical Information Service.


If your address has changed, or if you wish to be removed from the mailing list, or if the addressee is no longer employed by your organization, please notify AFGL/DAA, Hanscom AFB, MA 01731. This will assist us in maintaining a current mailing list.

Do not return copies of this report unless contractual obligations or notices on a specific document requires that it be returned.

SECONITY CENSSIPICATION OF THIS PAGE	REPORT DOCUM	ENTATION I	PAGE		
18 REPORT SECURITY CLASSIFICATION		16 RESTRICTIVE	MARKINGS		
Unclassified 2a SECURITY CLASSIFICATION AUTHORITY		3 DISTRIBUTION	AVAILABILITY O	F REPORT	
		Approve	d for publ	lic rele	ase:
2b. DECLASSIFICATION / DOWNGRADING SCHEDU	LE .		ution unli		
4 PERFORMING PRGANIZATION REPORT NUMBE	R(S)	5. MONITORING	ORGANIZATION R	EPORT NUMB	ER(S)
OMI-181		AFGL-TR	-86-0266		
Se NAME OF PERFORMING ORGANIZATION	66 OFFICE SYMBOL	7a NAME OF M	ONITORING ORGA	NIZATION	
OptiMetrics, Inc.	(If applicable)	Air Force	Geophysic	s Labor	atory
6c ADDRESS (City, State, and ZIP Code)	L	76 ADDRESS (Cit	ly, State, and ZIP	Code)	
121 Middlesex Turnpike		Hanscom	AFB, MA O	1731	
Burlington, MA 01803			-		
Ba NAME OF FUNDING/SPONSORING	Bb OFFICE SYMBOL	9 PROCUREMEN	T INSTRUMENT ID	ENTIFICATION	NUMBER
ORGANIZATION Air Force Geophysics Lab	(# applicable) OPA	F19628-8	5-C-0178		
Bc ADDRESS (City, State, and ZIP Code)	<u> </u>	10 SOURCE OF	FUNDING NUMBE	RS	
Hanscom AFB, MA 01731		PROGRAM ELEMENT NO	PROJECT NO	TASK NO.	WORK UNIT ACCESSION NO.
		62101F	7670	15	AI
SCIENTIFIC No. 2 M	18 SUBJECT TERMS (14 DATE OF REPORT 1986 Deci	ember		AGE COUNT 88 block number)
FIELD GROUP SUB-GROUP	Lidar Lasers				
		otical pro	perties		
An examination of investment of the system has been made. could be used with the line a Rayleigh atmosphaw relationship between In an atmosphere with relationship is tenuous to conclude that the pusupport its extensive use the atmosphere and different of power law parametrics.	ersion technic The purpose idar system under with no considerate in a cons	ques applinas been to der develor minimal and ext clouds, texamination ationship plication faerosols	o recommend opment by gaseous a inction exhemely nof the has no probing direction, one can	nd a tec AFGL. absorpti xists in tion of literatu physical ifferent	ion, a power which k=1. a power law are leads us leads to regions of the a single
20 DISTRIBUTION / AVAILABILITY OF ABSTRACT		Unclass		× 1	
220 NAME OF RESPONSIBLE INDIVIDUAL Eric Shettle		226 TELEPHON 617-37	E (Include Area Co 7 - 3665	AFGL	CE SYMBOL OPA
والمرابع المرابع المرابعة والمرابعة والمرابعة والمرابعة والمرابعة والمرابعة والمرابعة والمرابعة والمرابعة	APR edition may be used i				TION OF THIS PAGE

Block 19 (Continued)

An alternate inversion approach has been presented based on fundamental radiative transfer characteristics of the atmosphere. The approach is rooted in fundamental physics but, still, does not eliminate the problem of more unknowns than equations. For the approach to be used, one must still make an assumption about the type of aerosol responsible for the lidar signal.



CARLO CALL DISCOUNTY OF THE PARTY OF THE PAR

			Cor	tent
1.	INTR	ODUCTIO	N	1
2.	FORM	ULATION	OF THE LIDAR INVERSION PROBLEM	3
	2.2	Homoge: The Ra	dar Equation neous Atmosphere tio Method	3 4 6
	2.4	Extinc 2.4.1 2.4.2	Law Relationship Between Scattering & tion Coefficients The "Klett Method" Mid-Field Solution The Validity of the Power Law	7 9 10
			Relationship	10
	2.5	Linear Scatte	Wavelength Dependence of Aerosol ring	18
	2.6		ability of the Available Inversion ques for Spaceborne Applications	22
3.	SIMU		OF INVERSIONS FROM A SPACEBORNE LIDAR	25
	3.1	Simula	ted Atmosphere	25
		3.1.1	Case 1 - Aerosol-free Atmosphere at 337 nm	34
		3.1.2	Case 2 - Aerosol-free Atmosphere at at 514.5 nm	34
		3.1.3	Case 2 Plus Background Stratsopheric Aerosols	39
		3.1.4	Case 2 Plus Clear Tropospheric Aerosols	44
		3.1.5	Case 2 Plus Combined Stratospheric and Tropospheric Aerosols	44
		3.1.6	Case 2 Plus Aged Volcanic Aerosols	53
		3.1.7	Case 2 Plus Fresh Volcanic Aerosols	53
		3.1.8	Case 2 Plus Combined Background Stratospheric and Fresh Volcanic Aerosols	59
	3.2		ting the Boundary Conditions in a "Real Situation	67
	3.3		y of Results Utilizing a Power Law	6.8

4.	AN ALTERNATE INVERSION APPROACH FOR A SPACE-BORNE LIDAR SYSTEM	7(
5.	SUMMARY OF INVERSION TECHNIQUES AND RECOMMENDATIONS FOR FUTURE WORK	79
	5.1 Summary of Results	75
	5.2 Recommendations for Future Research	76
REF	ERENCES	7:

Illustrations

1.	Backscatter and Extinction Coefficients for Different AFGL Aerosol Models At (a.) 0.53 microns and (b.) 10.59 microns	15
2.	Backscatter and Extinction Coefficients At 0.55 micror for Representative Background Stratospheric Aerosols Aged Volcanic Aerosols and Fresh Volcanic Aerosols (Shettle, private communication)	
3.	Backscatter and Extinction Coefficients As A Function of Wavelength for (a.) Background Stratospheric Aerosols, (b.) Aged Volcanic Aerosols and (c.) Fresh Volcanic Aerosols	1 21
4.	(a.) Backscatter and (b.) Extinction Coefficients As a Function of Altitude for a Midlatitude Summer, Aerosol-free Atmosphere at 337 nm	27
5.	(a.) Backscatter and (b.) Extinction Coefficients As a Function of Altitude for a Midlatitude Summer, Aerosol-free Atmosphere at 514.5 nm	4 28
6.	Backscatter Coefficients As A Function of Extinction Coefficients at 337 nm For An Aerosol-free Atmosphere	29
7.	Extinction, Scattering and Absorption Coefficients As A Function of Altitude at 337 nm	30
8.	Backscatter Coefficients As A Function of Extinction Coefficients at 514.5 nm For An Aerosol-free Atmosphere	32
9.	Comparison of Simulated and Inverted Data at 337 nm for an Aerosol-free Atmosphere for the (a.) Near-field and (b.) Far-field Solutions	34
10.	Inverted Results at 337 nm with Variations in the Boundary Conditions Considered for (a.) Near-field and (b.) Far-field Solutions	36
11.	Comparison of Simulated and Inverted Data at 514.5 nm for an Aerosol-free Atmosphere for the (a.) Near-field and (b.) Far-field Solutions	37
12.	Inverted Results at 514.5 nm with Variations in the Boundary Conditions Considered for (a.) Near-field and (b.) Far-field Solutions	38

13.	Function of Altitude for a Midlatitude Summer Atmosphere at 514.5 nm With Background Stratospheric Aerosols	
14.	Backscatter Coefficients As A Function of Extinction Coefficients at 514.5 nm For A Midlatitude Summer Atmosphere With Background Stratospheric Aerosols	41
15.	Comparison of Simulated and Inverted Data at 514.5 nm for Case 3 For Various Values of k for the (a.) Near-field and (b.) Far-field Solutions	42
16.	Inverted Results at 514.5 nm with Variations in the Boundary Conditions Considered for Case 3 for the (a.) Near-field and (b.) Far-field Solutions	43
17.	(a.) Backscatter and (b.) Extinction Coefficients As A Function of Altitude for a Midlatitude Summer Atmosphere at 514.5 nm With "Clear" Tropospheric Aerosols	45
18.	Backscatter Coefficients As A Function of Extinction Coefficients at 514.5 nm For A Midlatitude Summer Atmosphere With "Clear" Tropospheric Aerosols	46
19.	Comparison of Simulated and Inverted Data at 514.5 nm for Case 4 For Various Values of k for the (a.) Near-field and (b.) Far-field Solutions	47
20.	Inverted Results at 514.5 nm with Variations in the Boundary Conditions Considered for Case 4 for the (a.) Near-field and (b.) Far-field Solutions	48
21.	(a.) Backscatter and (b.) Extinction Coefficients As A Function of Altitude for a Midlatitude Summer Atmosphere at 514.5 nm With Background Stratospheric and "Clear" Tropospheric Aerosols	
22.	Backscatter Coefficients As A Function of Extinction Coefficients at 514.5 nm for a Midlatitude Summer Atmosphere With Background Stratospheric Aerosols and "Clear" Tropospheric Aerosols	50
23.	Comparison of Simulated and Inverted Data at 514.5 nm for Case 5 for Various Values of k for the (a.) Near-field and (b.) Far-field Solutions	51
24.	Inverted Results at 514.5 nm with Variations in the Boundary Conditions Considered for Case 5 for the (a.) Near-field and (b.) Far-field Solutions	52

25.	(a.) Backscatter and (b.) Extinction Coefficients As A Function of Altitude for a Midlatitude Summer Atmosphere at 514.5 nm With Aged Volcanic Aerosols	A 54
26.	Backscatter Coefficients As A Function of Extinction Coefficients at 514.5 nm for a Midlatitude Summer Atmosphere With Aged Volcanic Aerosols	55
27.	Comparison of Simulated and Inverted Data at 514.5 nm for Case 6 For Various Values of k for the (a.) Near-field and (b.) Far-field Solutions	56
28.	Inverted Results at 514.5 nm with Variations in the Boundary Conditions Considered for Case 6 for the (a.) Near-field and (b.) Far-field Solutions	57
29.	(a.) Backscatter and (b.) Extinction Coefficients As a Function of Altitude for a Midlatitude Summer Atmosphere at 514.5 nm With Fresh Volcanic Aerosols	
30.	Backscatter Coefficients As A Function of Extinction Coefficients at 514.5 nm for a Midlatitude Summer Atmosphere With Fresh Volcanic Aerosols	60
31.	Comparison of Simulated and Inverted Data at 514.5 nm for Case 7 For Various Values of k for the (a.) Near-field and (b.) Far-field Solutions	61
32.	Inverted Results at 514.5 nm with Variations in the Boundary Conditions Considered for Case 7 for the (a.) Near-field and (b.) Far-field Solutions	62
33.	(a.) Backscatter and (b.) Extinction Coefficients As A Function of Altitude for a Midlatitude Summer Atmosphere at 514.5 nm With 50 % Background Stratospheric and 50 % Fresh Volcanic Aerosols	A 63
34.	Backscatter Coefficients As A Function of Extinction Coefficients at 514.5 nm for a Midlatitude Summer Atmosphere With Background and Fresh Volcanic Aerosols	64
35.	Comparison of Simulated and Inverted Data at 514.5 nm for Case 8 For Various Values of k for the (a.) Near-field and (b.) Far-field Solutions	65
36.	Inverted Results at 514.5 nm with Variations in the Boundary Conditions Considered for Case 8 for the (a.) Near-field and (b.) Far-field Solutions	66
37.	Inverted Results at 514.5 nm with the Alternate Inversion Techniques for a Simulated Atmosphere with Aged Aerosols	72

38. Inverted Results at 514.5 nm with Variations in (a.) the Single Scattering Albedo and (b.) the Fraction of Backscattered Radiation

73

Tables

1;	A Partial Examination of the History of the Power Law Assumption Relating Backscatter and Extinction	12
2.	Values of the Exponent k Required to Fit the AFGL Boundary Layer Aerosol Models Shown in Figure 1 (a. With A Power Law Over the Given Relative Humidity Ranges	16
3.	Summary of Results of Evans ¹⁸ Relating to Power Law Relationships Between Backscatter and Extinction	19
4.	Summary of Examination of Inversion Techniques for Use With A Space-borne Lidar System	23
5.	Details of the AFGL Lidar System and the Test Flight From the White Sands Missile Range, NM	26
6.	Test Cases Used in the Lidar Simulation	33

1. INTRODUCTION

Laser radars, or lidars, are powerful tools for probing the atmosphere. They have been used, for example, in studies to probe for the presence of aerosols in the atmosphere, to obtain the profiles of absorbing gases such as water vapor and as a wind measuring tool. Theoretical studies have also been done to investigate the possibility of using lidars to invert the temperature structure of the atmosphere. In the past, the lidars have been typically used from ground-based platforms looking upwards or horizontally. A few studies have also utilized lidars mounted in aircraft or on balloons. Some of these latter studies have focused on preparing lidars for eventual use on space shuttles or satellites.

The Air Force Geophysics Laboratory (AFGL) is developing a lidar system to be flown on the Defense Meteorological Satellite Platforms (DMSP) series of meteorological satellites. The lidar system is being designed to study the optical properties of the atmosphere as well as to measure wind and composition.

The reflected laser energy can be used to invert information about the optical properties of the atmosphere. The techniques used to invert this information are the subject of this report. Chapter 2 examines the mathematical formulation of the inversion problem and presents the inversion techniques commonly used by researchers. Chapter 3 presents and compares results from a simulated spaceborne lidar

system utilizing one of the commonly used inversion techniques. Chapter 4 presents a proposal for an inversion
technique that addresses the needs and goals of a spaceborne lidar system. Finally, chapter 5 summarizes our results and conclusions.

2. FORMULATION OF THE LIDAR INVERSION PROBLEM

2.1 The Lidar Equation

The received signal for a single wavelength lidar system is described by the equation

$$P(r) = P_0 \frac{rc}{2r^2} A \beta(r) \exp \left[-2 \int_0^r \sigma(r') dr'\right]$$
 (1)

where P(r) is the instantaneous received power from the range r, P_{O} is the transmitted power of the laser over the pulse length r, c is the speed of light, A is the effective system receiver area, $\beta(r)$ and $\sigma(r)$ are the backscatter and extinction coefficients, respectively. The equation (1) is commonly known as the lidar equation. In the above, the backscatter and extinction coefficients include contributions from all sources, molecular and particulate. The equation also assumes a single scattering atmosphere. Although not done at this time, (1) can be broken down to include the separate contributions. A more manageable form of the lidar equation can be established by defining a quantity, S(r), that is the logarithmic range-adjusted power

$$S(r) = ln[r^2p(r)]$$
 (2)

Utilizing this quantity eliminates system dependent parameters from the lidar equation. The new form of the lidar equation then becomes

$$S-S_o = \ln[\beta/\beta_o] - 2 \int_{r_o}^{r} dr'$$
 (3)

where $S_O = S(r_O)$, $\beta_O = \beta(r_O)$ and r_O is a constant reference range. The differential equation corresponding to equation (3) is

$$dS/dr = 1/\beta (d\beta/dr) - 2\sigma$$
 (4)

One of the goals of using lidars to probe the atmosphere is to invert information about the optical parameters, $^\sigma$ and $^\beta$. However, a crucial problem is faced when inverting the lidar equation in that it contains two unknown variables, the backscatter and extinction coefficients, and only one equation. In order to eliminate the problem of one equation and two unknowns, researchers have made assumptions about the relationship between σ and β . We shall now examine some of the assumptions made concerning σ and β to put the lidar equation into a form that can be inverted. The implications of the assumptions will be discussed along with the advantages and disadvantages of each approach.

2.2 Homogeneous Atmosphere

If one assumes that the atmosphere is homogeneous, then $d \beta / dr = 0$ and equation (4) reduces to

The assumption of $d\beta/dr = 0$ gives rise to what is called the slope method of inversion. The value of the homogeneous extinction coefficient is evaluated as the slope of the least squares fit of the S(r) data. An obvious requirement for the use of the slope method is that dS/dr be negative otherwise negative values of the extincient coefficient will be obtained.

The slope method has been used by Murray¹ with an infrared lidar system. In their study they used a CO₂ lidar that operated at four wavelengths near 10.3 microns. The system operated over horizontal paths and was conceived as a way to measure visibility for aircraft landing operations. Their study indicated that a single-ended measurement approach yielded results that agreed with other measurements for ranges up to 10 km. For additional details on the slope method, the interested reader is referred to the papers by Collis² and Viezee³.

Murray, E. R., M. F. Williams and J. E. van der Laan (1978) Single-ended Measurement of Infrared Extinction Using Lidar, <u>Applied Optics</u>, <u>17</u>:296.

Collis, R. T. H. (1966) Lidar: A New Atmospheric Probe,
 Q. J. R. Meteorol. Soc. 92:220.

^{3.} Viezee, W., E. E. Uthe and R. T. H. Collis (1969) Lidar Observations of Airfield Approach Conditions: An Exploratory Study, J. Appl. Meteorol. 8:274.

2.3 The Ratio Method

The atmosphere is unlikely to be homogeneous over the entire path being probed by a lidar, especially a space-borne platform. However, the atmosphere may be nearly homogeneous over small intervals of the path. In this case, one can apply a form of the slope method over the small, nearly homogeneous layers and then build up an approximation of the profile of $\sigma(r)$. This method, known as the ratio or slice method of inversion assumes homogeneity within each layer, yet relaxes the condition that the extinction coefficient is constant. The extinction coefficient is then given as 4,5,6

$$\sigma(r_{i}) = \frac{1}{2\Delta r_{i}} \ln[r_{i}^{2} P(r_{i})/r_{i+1}^{2} P(r_{i+1})]$$
 (6)

where the subscripts i and i+l refer to the small, nearly homogeneous layers and Δr_i is the distance between the layers.

The assumption of a homogeneous or near homogeneous atmosphere suits this method primarily to horizontal viewing paths, such as would be used for aircraft visibility operations. The technique could also be used for low elevation

^{4.} Kohl, R. H. (1978) Discussion of the Interpretation Problem Encountered in Single-Wavelength Lidar Transmissometers, J. Appl. Meteor., 17:1034.

^{5.} Brown, Jr., R. T. (1979) Comments on "Discussion of the Interpretation Problem Encountered in Single -Wavelength Lidar Transmissometers, J. Appl. Meteor., 18:711.

^{6.} Kohl, R. H. (1979) Reply, J. Appl. Meteor., 18:712.

slant paths if it was known beforehand that the medium being studied did not have sharp boundaries below any critical altitude levels. However, before applying the ratio or slope techniques, one must be reasonably sure that homogeneity exists⁶. Unfortunately, for many interesting situations such as dense cloud, fog, smoke and dust, these methods cannot be used. Even under stable conditions in fogs, local heterogeneities occur, thus invalidating the inversion process.

Looking down from space, the atmospheric density is exponentially increasing. The slope method will then be, by definition, inappropriate. The ratio method, however, could be utilized if the data were devoid of large fluctuations. Unfortunately, the large fluctuations can result from scientifically interesting phenomena such as aerosol layers or clouds. (The presence of these "scientifically interesting phenomena" can further complicate the inversion process by introducing multiple scattering effects for which there is not current accounting.)

2.4 Power Law Relationship Between Scattering & Extinction Coefficients

It has been suggested that under certain conditions the backscatter and extinction coefficients can be related by a power law expression of the form

$$\beta = c \sigma^{k} \tag{7}$$

where c is a constant and k depends upon the wavelength of the lidar and the properties of the obscuring medium. Assuming that the power law relationship is valid, the lidar equation can be given as

$$dS/dr = (k/\sigma)d\sigma/dr - 2\sigma$$
 (8)

This is a form of the Bernoulli or homogeneous Ricatti equation which has the general solution 7

$$\sigma^{-1} = \exp \left[-\int \frac{1}{k} \frac{ds}{dr'} dr' \right]$$

$$\times \left[c - 2/k \int_{-\infty}^{\infty} \exp \left(-\int \frac{1}{k} \frac{ds}{dr'} dr' \right) dr' \right]$$
(9)

Assuming k to be constant, the solution may be simplified to the following

$$\sigma = \frac{\exp [(S - S_0)/k]}{\left[\sigma_0^{-1} - 2/k \int_{r_0}^{r} \exp [(S - S_0)/k] dr'\right]}$$
(10)

This is sometimes known as the near-field solution. This solution is not a new one. It has been known for a number of years but, for horizontal or upward looking paths, the solution can be plagued with instability problems that result in questionable and/or unrealistic results. This

^{7.} Klett, J. D. (1981) Stable Analytical Inversion Solution for Processing Lidar Returns, Applied Optics 20:211.

happens despite the fact that both the numerator and the denominator approach zero at nearly the same rate. The denominator tends to zero as the difference of two large numbers, creating a highly unstable situation. (A more detailed discussion of the instabilities inherent in (10) can be found in Klett⁷.)

2.4.1 The "Klett Method"

Klett has proposed an alternate solution to (10) in which the integration constant in (9) is evaluated in terms of a range $r_{\rm m}$ far from the lidar. Under this assumption, the solution is generated for ranges less than $r_{\rm m}$ rather than ranges greater than $r_{\rm o}$ as in the case of (10). Klett's approach, that utilizes what is known as the far-field solution, is given as

$$\sigma = \frac{\exp \left[(S - S_m)/k \right]}{\left[\sigma_m^{-1} + 2/k \int_r^{rm} \exp \left[(S - S_m)/k \right] dr' \right]}$$

This solution form of the Bernoulli equation is what is often known as "the Klett method." In a further modification to his solution, Klett⁸ allows for a variable backscatter-extinction ratio and the inclusion of Rayleigh scattering. Although similar in form to the near-field solution, it has

^{8.} Klett, J. D. (1985) Lidar Inversion with Variable Backscatter/Extinction Ratios, Applied Optics 24:1638.

been found by many researchers^{9,10} to be more stable than the near-field solution. However, the majority of studies that have utilized the "Klett method" have employed horizontal or upward looking orientations.

2.4.2 Mid-Field Solution

Ferguson and Stephens¹¹ have proposed a futher alternative to the near-field solution that utilizes the stability of the Klett algorithm to calculate a boundary value at some middle range. In their original proposal, an iterative approach was employed to calculate an accurate far-field boundary condition. Mulders¹² later pointed out that the iterative approach could be replaced with an analytic solution.

2.4.3 The Validity of the Power Law Relationship

The power law relationship allows the researcher to work with an equation with a known solution. The use of the "Klett method" offers mathematical stability. However, use of the power law presupposes knowledge of the attenuating medium being studied. In addition to "throwing the baby out

^{9.} Hughes, H. G., J. A. Ferguson and D. H. Stephens (1985)
Sensitivity of a Lidar Inversion Algorithm to
Parameters Relating Atmospheric Backscatter and
Extinction, Applied Optics, 24:1609.

^{10.} Bissonnette, L. R. (1986) Sensitivity Analysis of Lidar Inversion Algorithms, Applied Optics, 25:2122.

^{11.} Ferguson, J. A. and D. H. Stephens (1983) Algorithm For Inverting Lidar Returns, Applied Optics, 22:3673.

^{12.} Mulders, J. M. (1984) Algorithm for Inverting Lidar Returns: Comment, Applied Optics, 23:2855.

with the bath water", the power law relationship is not valid for all types of media that might be encountered by a spaceborne lidar system.

In all fairness to Klett, he stated in his original paper (see page 212 of Klett⁷) that the use of the power law relationship is not appropriate for all aerosol types or wavelengths. Considering that so many researchers have been utilizing the power law relationship, it seems reasonable to examine the history of the power law relationship between backscattering and extinction. The results of that examination are summarized in Table 1.

Curcio and Knestrick 13 are one of the earliest sources for the power law relationship between backscattered radiation and attenuation. In their paper, they correlated backscattering and atmospheric transmission from a series of horizontal measurements through fog, rain, drizzle, snow and clear air and found that an empirical relationship of the form $\beta = c \ \sigma^{0.66}$ fit their data. Their data were taken for white light conditions rather than for mononchromatic radiation, such as one would have with a laser. The authors also note that their relationship will not hold in "industrially contaminated air."

There is no <u>a priori</u> reason to assume that the back-scatter and extinction coefficients would be related by a

^{13.} Curcio, J. A. and G. L. Knestrick (1958) Correlation of Atmospheric Transmission and Backscattering, J. Opt. Sci. Am., 48:686.

Table 1. An Examination of the History of the Power Law Assumption Relating Backscatter and Extinction

AUTHOR(8)	PINDINGS
Curcio and Knestrick 13	From Measurements of Visibility in Clean Air A Relationship of the Form
	Range = Jonstant x Backscatter 1.5
	Was Found to Be Valid Within About 20 %
Twomey and Bowell 14	From a Theoretical Study Using Four Types of Size Distributions: 1. A Relationship, but not An Unique One, Exists Between Backscattering & Extinction
	2. The Relationship Holds Better For White Light Rather Than Monochromatic Radiation
renn 15	From A Theoretical Examination Concludes That No General Relationship Exists Between Backscatter and Extinction - The Variety of Aerosol Formation and Decay Processes Leads to Different Relationships
Pinnick et. al. ¹⁶	From A Theoretical Examination of Water Clouds Conclude That An Approximate Relationship Can Be Found Between Backscatter and Extinction for Visible and Near-infrared Radiation
Mulders ¹²	Measurements Indicated Rapid Changes Can Occur in Backscatter and Extinction Relationships

Twomey, S. and H. B. Howell (1965) The Relative Merit of White and Monochromatic Light for the Determination of Visibility by Backscattering Measurements, Applied Optics, 4:501.

14.

unique power law relationship. Fenn 15 has pointed out that only with a combination of changes in number densities and size distributions can one get a power law relationship between backscattering and extinction. If the aerosol size distributions, complex indices of refraction and particle shapes were all constant then one could assume a power law relationship. However, aerosols and clouds are highly variable phenomena with strong shape, altitude, humidity, composition and meteorological (e.g. wind) dependencies. Even if power law relationships did exist for the aerosols and clouds, one would not know which set of values, k and c, to use because clouds and aerosols can be found at the same Also, Mulders 12 has altitudes, often at the same times. shown that power law relationships, if they can be obtained, can be fitted to data but that the values of the relevant parameters can change as a function of time. Mulders concludes from a series of horizontal measurements over the ocean that the power law parameters are not constant for more than a few hours.

Pinnick et. al. 16 have presented results from calculations of backscatter and extinction through stratus and cumulus clouds. Their zero order solution (their term) calculations were performed for 156 measured cloud droplet

^{15.} Fenn, R. W. (1966) Correlation Between Atmospheric Backscattering and Meteorological Range, <u>Applied Optics</u>, 5:293.

^{16.} Pinnick, R. G., S. G. Jennings, P. Chylek, C. Ham and
W. T. Grandy, Jr. (1983) Backscatter and Extinction in
Water Clouds, J. Geophys. Res., 88:6787.

distributions for visible, near IR and IR wavelengths. They found that a linear relationship exists between backscatter and extinction at 0.6328 μ m but that none exists at 10.6 μ m.

Shettle 17 has presented results of backscatter and extinction coefficient comparisons for the tropospheric aerosol models in LOWTRAN 6 as a function of relative humidity. His calculated results for the wavelengths 0.53 and 10.59 μ m are reproduced as Figures 1 (a.) and (b.), respectively. Each point on the curves represents a different relative humidity. Table 2 gives the corresponding exponents required to fit the data in Figure 1 (a.) with a power law over the given relative humidity ranges. (The attenuation coefficients increase with relative humidity.) His results demonstrate that a power law relationship is not appropriate for tropospheric aerosols except over very limited relative humidity ranges and for given wavelengths. Figure 2 shows similar results for the AFGL stratospheric aerosol models. The three points refer to representative background stratospheric conditions, aged volcanic aerosols and fresh volcanic aerosols [Shettle, private communication, 1986]. Again, a unique power law relationship does not exist for In a realistic situation, stratospheric aerosols. stratosphere could contain all three types of aerosols with three different characteristic indices of refraction and size distributions.

^{17.} Shettle, E. P. (1985) Backscattering by Atmospheric Aerosols, Presented at the IAMPA/IAPSO Joint Assembly, Honolulu, Hawaii, 5-16 August 1985.




Figure 1. Backscatter and Extinction Coefficients for Different AFGL Aerosol Models At (a.) 0.53 microns and (b.) 10.59 microns

Table 2. Values of the Exponent k Required to Fit the AFGL Boundary Layer Aerosol Models Shown in Figure 1 (a.) With A Power Law Over the Given Relative Humidity Ranges

Aerosol Type	Relative 0 - 70		Range (%) 80 - 99
Rural	-0.4	0.09	0.9
Maritime	0.7	0.9	1.2
Urban	1.2	1.2	1.2
Tropospheric	0.05	0.1	0.7




Figure 2. Backscatter and Extinction Coefficients At 0.55 microns for Representative Background Stratospheric Aerosols, Aged Volcanic Aerosols and Fresh Volcanic Aerosols (Shettle, private communication)

Evans 18 has confirmed the results of Shettle 17 and extended the analysis to other aerosol types. Evans performed calculations of the backscatter/extinction ratio using Mie theory for a large range of values of the real and imaginary components of the index of refraction and the modal size parameter. His results are summarized in Table 3 and can be used by researchers to determine for what wavelengths and size distributions one could utilize a power law relationship.

2.5 Linear Wavelength Dependence of Aerosol Scattering

The use of more than one laser wavelength increases the amount of information about the medium being studied. Utilizing frequency doubling and tripling techniques, one can, for instance, use one laser line to provide information about the molecular components of the atmosphere, thereby helping to define the background atmospheric signal, and use a second line to study aerosol contributions.

DeLuisi et.al. 19 have proposed using a dual or triple wavelength lidar system in which the aerosol scattering is

^{18.} Evans, B. T. N. (1986) Sensitivity of the Lidar Ratio to Changes in Size Distribution and Index of Refraction, Thirteenth International Laser Radar Conference, NASA Conference Publication 2431, National Aeronautics and Space Administration, Code NIT-4, Washingtion, D. C.

^{19.} DeLuisi, J. J., Schuster, B. G. and Sato (1975)
Separation of Dust and Molecular Scattering
Contributions to the Lidar Observation: A Method,
Applied Optics 14:1917.

Table 3. Summary of Results of Evans 18 Relating to Power Law Relationships Between Backscatter and Extinction Coefficients Table 3. Summary of Results of Eva Backscatter and Extinction Coeffici

200

25.50 Cent

The Ratio of Backscatter to Extinction Coefficients Is Insensitive to Changes in the Size Distribution:	The Ratio of Backscatter to Extinction Coefficients Is Sensitive to Changes in the Size Distribution:
For Small Non-absorbing Particles	For Water Droplets with Modal Size Parameters < 2 and Wavelengths in the
For Water Droplets with a Modal Particle Size Greater than 1 micron and Visible E	Range 0.2 - 12 microns
Near-infrared Wavelengths	For Rural or Maritime Type Aerosols at Any Wavelength in the Visible & Infrared
For Water Droplets with a Modal Particle Size Greater than 10 microns and	For Water Droplets with Darticle Sizes
-	on the Order of Several Microns &
Real Part of Index of Refraction = 1.5, Imaginary Part $\leq 10^{-4}$ and the Modal Size Parameter, $x_m \geq 6$	Far-intrared Wavelengths Hygroscopic Aerosols and Relative Humidity Above 70 %
$2kX_m \ge 1$	

$$x_{m} = (2 \tau R_{m} / \lambda)$$

k = Imaginary Part of Index of Refraction

linearly related. With their formulation, the scattering coefficient for wavelength i is given as

$$\beta(r)_{i} = [1 + c (\lambda_{1} - \lambda_{i})/(\lambda_{1} - \lambda_{3})] \beta(r)_{1}$$

$$i = 1, 2, 3$$
(12)

where λ is the wavelength. Utilizing this assumption DeLuisi et.al. were able to develop an inversion technique with equal numbers of equations and unknowns that would allow one to obtain a separate inversion of molecular and aerosol optical properties.

The key to the DeLuisi et. al. approach is the assumption that a linear relationship exists relating the aerosol extinction properties at different wavelengths. Figure 3 displays the wavelength dependence of the aerosol extinction and scattering coefficients for the background stratospheric, aged volcanic and fresh volcanic aerosol models used in the AFGL model atmospheres (Shettle, private communication). (For the background stratospheric conditions the extinction and backscatter coefficients overlap.) The figures show that the wavelength dependences are not necessarily linear and that they differ from one aerosol type to another. This being the case, one would have to guess the type of aerosol being probed in order to incorporate the appropriate wavelength dependence.




Figure 3. Backscatter and Extinction Coefficients As A Function of Wavelength for (a.) Background Stratospheric Aerosols, (b.) Aged Volcanic Aerosols and (c.) Fresh Volcanic Aerosols

2.6 Applicability of the Available Inversion Techniques for Spaceborne Applications

Table 4 summarizes the results from the examination of the various inversion techniques from the perspective of a spaceborne lidar system. The table lists the fundamental assumptions of each of the techniques, advantages and disadvantages.

The slope and ratio methods offer simplicity but are not appropriate for a spaceborne system. The slope method cannot be used because the viewing path is inhomogeneous (i.e. exponentially increasing). The ratio method also can not be used because the degree of inhomogeneity gives rise to negative attenuation coefficients.

The inversion technique that is commonly used researchers is based on the power law assumption with the "Klett technique" for the solution. The assumption of a power law relationship yields an equation with a known The "Klett" approach is used rather than the solution. near-field solution because of its supposed improvements in stability. The use of the word "supposed" is deliberate. The studies to-date with the "Klett" technique have not demonstrated that the far-field solution is inherently more stable than the near-field solution. The studies to-date have primarily involved horizontal or upward looking path configurations and it may be that the choice of path configuration determines the stability characteristics of a given form of a Bernoulli equation solution. Kastner and

Table 4. Summary of Inversion Techniques for Use With a Spaceborne Lidar System

MOTOGOVIT			
TECHNIQUE	ASSUMPTION(s)	ADVANTAGES	DISADVANTAGES
Slope Method	Homogeneous Atmosphere Over Entire Path	Simple Solution	Not Applicable (Atmosphere is Inhomogeneous)
Ratio Method	Homogeneous Atmosphere Over Portions of Path	Allows Limited Inhomogeneity	Not Applicable (Gives Negative Values of Extinction)
Power Law	Backscatter-Extinction Related By A Power Law	Analytic Solution	No Physical Basis
		Can Be Used to Estimate Optical Properties	No One Power Law for Entire Atmosphere Can Change Quickly
"Far-field" Solution		More Stable for Horizontal and Ground Up Paths	Difficult to Accurately Calculate Boundary Conditions
"Near-field" Solution		Improved Stability for Downward Paths Easier to Estimate Boundary Conditions	More Sensitive to Variations in k
DeLuisi et, a	al. Aerosol Properties Linearly Related by Wavelength	Gives A Complete Set of Equations	Aerosols Not Linearly Related By Wavelength Need to Know the Relationship In Advance

Quenzel²⁰ have examined the usefulness of the near- and far-field algorithms in the context of a downward-looking, spaceborne lidar system. Their results indicate that in an atmosphere with low turbidity the near-field solution yields better results than a far-field solution. In an atmosphere with high turbidity, they found that the far-field solution gave better results.

The next chapter presents results from a simulated downward looking spaceborne system that utilizes a power law approach for inversion. Results from both near- and farfield solutions will be presented in order to gauge the superiority, if any, of one solution approach over another.

^{20.} Kastner, M. and H. Quenzel (1986) The Usefulness of Klett's Inversion Algorithms to Simulated Satellite Lidar Returns, Thirteenth International Laser Radar Conference, NASA Conference Publication 2431, National Aeronautics and Space Administration, Code NIT-4, Washington, D. C.

3. SIMULATION OF INVERSIONS FROM A SPACEBORNE LIDAR SYSTEM

The simulation is intended to be representative of data taken from the lidar system under development by AFGL. A version of the system has been flown on a high altitude balloon from the White Sands Missile Range, New Mexico. The features of the lidar system and the test flight are summarized in Table 5 (Bedo, private communication, 1986).

3.1 Simulated Atmosphere

Lidar signals from a midlatitude summer atmosphere under a variety of conditions are being simulated. A midlatitude summer atmosphere was chosen as being most representative of the conditions at the time of the launch. Tabulated optical parameters at 337 and 514.5 nm were taken from the work of McClatchey et. al. 21 for this study. These wavelengths were assumed to be close enough to the actual lidar lines for the purpose of this study.

The scattering and extinction coefficients for an aerosol-free atmosphere at 337 and 514.5 nm are shown in Figures 4 and 5, respectively. The 337 nm extinction coefficients include molecular absorption from ozone as well as Rayleigh scattering. As shown in Figure 6, the data do not exhibit a linear relationship that corresponds to a power law of k=1. Figure 7 shows the individual components

^{21.} McClatchey, R. A., R. W. Fenn, J. E. A. Selby, F. E. Volz and J. S. Garing (1972) Optical Properties of the Atmosphere, Air Force Cambridge Research Laboratories, Hanscom Field, Bedford, Massachusetts, AFCRL-72-0497, AD753075.

Details of the AFGL Lidar System and the Test Flight From the White Sands Table 5. Details Missile Range, NM

PARTICIPATION OF THE PERSONS IN

Wavelengths	355 and 532 nm
Field of View	2 1/2 milliradians. Lidar looks up, down and 2 degrees above horizon
Altitude Resolution	150 meters
Pulse Rate	10 pulses per second. (Data averaged over 10 pulses to smooth out expected 10 % deviation between pulses.)
Date of Flight	24 Aug 1984
Balloon Float Altitude 33 Km	33 Km
Weather Support Data	Radiosonde data taken from Roswell, NM at 2130 LST. No moonlight reported.

Aerosol Free Atmosphere - 337nm (a) 0.002 0.004 0.006 0.008 0.01 Backscatter Coefficient (km - 1)

Figure 4. (a.) Backscatter and (b.) Extinction Coefficients As A Function of Altitude for a Midlatitude Summer, Aerosolfree Atmosphere at 337 nm

0.04

Extinction Coefficient (km -1)

0.06

80.0

0.02

(b)




Figure 5. (a.) Backscatter and (b.) Extinction Coefficients As A Function of Altitude for a Midlatitude Summer, Aerosolfree Atmosphere at 514.5 nm




Figure 6. Backscatter Coefficient As A Function of Extinction Coefficients at 337 nm For An Aerosol-free Atmosphere




Figure 7. Extinction, Scattering and Absorption Coefficients As A Function of Altitude at $337\ \mathrm{nm}$

as a function of altitude. The 514.5 nm values consist of Rayleigh scattering only and correspond to a power law relationship in which k=1, as shown in Figure 8. At both wavelengths, the scattering coefficients are those at a backscattering angle of 180 degrees.

The results to be presented are referenced to a space-borne platform. Therefore, the near-field solution refers to a solution that begins at high altitudes and proceeds toward the surface. The far-field solution begins at or near the surface and proceeds towards the spacecraft.

The simulations will be performed for the eight cases listed in Table 6. It is assumed that the short wavelength laser line would be used primarily to define the molecular components of the atmosphere and that the visible line would be used for aerosol studies. Under this assumption, one would invert the shorter wavelength data first to determine the gaseous components and then invert the visible data to extract any aerosol information.

In the results that follow it is assumed that the near-and far-field boundary conditions are known accurately. Results will also be presented in which the boundary conditions are perturbed by +/- 10 and 40 % to determine the effects of inaccuracies in the boundary conditions on the inversion algorithms.

Aerosol-Free Atmosphere - 514.5nm




Figure 8. Backscatter Coefficients As A Function of Extinction Coefficients at 514.5 nm For An Aerosol-free Atmosphere

Table 6. Test Cases Used in the Lidar Simulation.

SOLDERONG CONTROL DOCUMENT PARTIES CONTROL CONTROL

CASE	CONDITIONS
1	Aerosol-Free Atmosphere at 337 nm
7	Aerosol-Free Atmosphere at 514.5 nm
m	Case 2 Plus Background Stratospheric Aerosols
4	Case 2 Plus Clear Tropospheric Conditions
ហ	Case 2 Plus Combined Stratospheric & Tropospheric Aerosols (Cases 3 & 4)
y	Case 2 Plus Aged Volcanic Aerosols
7	Case 2 Plus Fresh Volcanic Aerosols
œ	Case 2 Plus Combined Background Stratospheric & Fresh Volcanic Aerosols

3.1.1 Case 1 - Aerosol-free Atmosphere at 337 nm

Figures 9 (a.) and (b.) show the results for an aerosol-free simulated atmosphere at 337 nm from the near-and far-field inversions, respectively. The results are given for k values of 0.8, 1.0 and 1.2. The differences between the inverted atmospheric data and the simulated atmosphere with k=1.0 are small for both the near- and far-field solutions with the differences being due to the presence of ozone absorption (see Figure 7).

Figure 10 shows the results of the inversions with changes in the boundary conditions considered. The near-field solution results, Figure 10 (a.), show a somewhat greater sensitivity to changes in the boundary conditions than do the far-field solution results, Figure 10 (b).

3.1.2 Case 2 - Aerosol-free Atmosphere at 514.5 nm

Figures 11 (a.) and (b.) show the results for a simulated atmosphere at 514.5 nm from the near- and far-field inversions, respectively. For both solution forms, a value of k=1 yielded the best solutions, as they should, seeing that the simulated data were based on a power law relationship between the extinction and backscattering. The differences shown in the curves are due to the linear fitting of the simulated data. Figures 12 (a.) and (b.) show the results with perturbations in the boundary conditions considered.




Figure 9. Comparison of Simulated and Inverted Data at 337 nm for an Aerosol-free Atmosphere for the (a.) Near-field and (b.) Far-field Solutions




Figure 10. Inverted Results at 337 nm with Variations in the Boundary Conditions Considered for (a.) Near-field and (b.) Far-field Solutions




Figure 11. Comparison of Simulated and Inverted Data at 514.5 nm for an Aerosol-free Atmosphere for the (a.) Near-field and (b.) Far-field Solutions

(大学の) 国際などの (国際などの) (大学などの) (大学などの) (大学などの) (日本の) (日




Figure 12. Inverted Results at 514.5 nm with Variations in the Boundary Conditions Considered for (a.) Near-field and (b.) Far-field Solutions

The preceding two sets of results demonstrate that a power law approximation will reproduce an atmosphere consisting of Rayleigh scatterers with little or no molecular absorption. The results to follow will examine the ability of a power law approach to accurately reproduce an atmosphere containing Rayleigh as well as non-Rayleigh components. It is presumed that the non-Rayleigh components are aerosols or clouds. The results will utilize the 514.5 nm laser line.

3.1.3 Case 2 Plus Background Stratospheric Aerosols

This case considers an atmosphere with background statospheric aerosols added to a background Rayleigh atmosphere. The aerosols are added between 10 and 25 km. Figures 13 (a.) and (b.) show, respectively, the backscatter and extinction coefficients for the case. The background aerosol-free values are dashed in for reference. Figure 14 gives the backscatter coefficients plotted against the extinction coefficients.

The near- and far-field inversions are shown in Figures 15 (a.) and (b.), respectively. In both the near- and far-field solutions, a profile based k=1 reproduces the simulated data above and below the aerosol layer. Figures 16 (a.) and (b.) show the sensitivity of each solution to changes in boundary conditions with a value of k=1.




Figure 13. (a.) Backscatter and (b.) Extinction Coefficients As A Function of Altitude for a Midlatitude Summer Atmosphere at 514.5 nm With Background Stratospheric Aerosols




Figure 14. Backscatter Coefficients As A Function of Extinction Coefficients at 514.5 nm For A Midlatitude Summer Atmosphere With Background Stratospheric Aerosols




Figure 15. Comparison of Simulated and Inverted Data at 514.5 nm for Case 3 For Various Values of k for the (a.) Near-field and (b.) Far-field Solutions




Figure 16. Inverted Results at 514.5 nm with Variations in the Boundary Conditions Considered for Case 3 for the (a.) Near-field and (b.) Far-field Solutions

3.1.4 Case 2 Plus Clear Tropospheric Aerosols

In this example, a layer of tropospheric aerosols is added between the surface and 10 km. The optical conditions correspond to a "clear" atmosphere. Figures 17 (a.) and (b.) show the backscatter and extinction coefficients as a function of altitude. Figure 18 shows the plot of the backscatter versus the extinction coefficients.

The results from the inversion with various values of k are shown in Figures 19 (a.) and (b.). Both approaches give good results with a k=1 power law for altitudes above 10 km. The near-field solution looks like a value of k between 0.8 and 1.0 will give a reasonable fit. The far-field solution has reasonable fit with k=0.8. Figures 20 (a.) and (b.) show the results with variations in the boundary condition considered. The results assumed k=1.

3.1.5 Case 2 Plus Combined Stratospheric and Tropospheric Aerosols

This case corresponds to the combination of the background stratospheric aerosols with the clear tropospheric aerosols from the preceding case. Figures 21 (a.) and (b.) show the backscatter and extinction coefficients, respectively, as a function of altitude. Figure 22 displays the backscatter coefficients plotted against the extinction coefficients.

Figures 23 (a.) and (b.) show the results of the inversion with $\,k$ varied and Figures 24 (a.) and (b.) show the results of the variation of the boundary conditions.




Figure 17. (a.) Backscatter and (b.) Extinction Coefficients As A Function of Altitude for a Midlatitude Summer Atmosphere at 514.5 nm With "Clear" Tropospheric Aerosols




Figure 18. Backscatter Coefficients As A Function of Extinction Coefficients at 514.5 nm For A Midlatitude Summer Atmosphere With "Clear" Tropospheric Aerosols




Figure 19. Comparison of Simulated and Inverted Data at 514.5 nm for Case 4 For Various Values of k for the (a.) Near-field and (b.) Far-field Solutions




Figure 20. Inverted Results at 514.5 nm with Variations in the Boundary Conditions Considered for Case 4 for the (a.) Near-field and (b.) Far-field Solutions




Figure 21. (a.) Backscatter and (b.) Extinction Coefficients As A Function of Altitude for a Midlatitude Summer Atmosphere at 514.5 nm With Background Stratospheric and "Clear" Tropospheric Aerosols




Figure 22. Backscatter Coefficients As A Function of Extinction Coefficients at 514.5 nm For A Midlatitude Summer Atmosphere With Background Stratospheric Aerosols and "Clear" Tropospheric Aerosols




Figure 23. Comparison of Simulated and Inverted Data at 514.5 nm for Case 5 For Various Values of k for the (a.) Near-field and (b.) Far-field Solutions




Figure 24. Inverted Results at 514.5 nm with Variations in the Boundary Conditions Considered for Case 5 for the (a.) Nearfield and (b.) Far-field Solutions

None of the k values tried yielded an acceptable fit to the simulated data. A value of k of 0.8 gave a reasonable fit to the far-field solution for altitudes below 10 km but an unacceptable fit above 10 km. This agrees with the results for the individual aerosols layers (see Sections 3.1.4 and 3.1.5). One can conclude from this, that one power law cannot represent an atmosphere with distinct aerosol layers.

3.1.6 Case 2 Plus Aged Volcanic Aerosols

Figures 25 (a.) and (b.) show the backscatter and extinction coefficients as a function of altitude for an atmosphere with aged volcanic aerosols added to an aerosolfree background. The backscatter and extinction coefficients, as shown in Figure 26, are those in LOWTRAN 6 [Shettle, private communication, 1986].

Figures 27 (a.) and (b.) give the results from the inversions with different values of k and Figures 28 (a.) and (b.) give the results from the variation in the boundary conditions with k=1. As with the background stratospheric aerosol results (e.g. Figure 15), a power law with k=1 will reproduce the aerosol-free parts of the atmosphere but not those with aerosols present.

3.1.7 Case 2 Plus Fresh Volcanic Aerosols

Figures 29 (a.) and (b.) show the backscatter and extinction coefficients as a function of altitude for an atmosphere with fresh volcanic aerosols added to an aerosol-




Figure 25. (a.) Backscatter and (b.) Extinction Coefficients As A Function of Altitude for a Midlatitude Summer Atmosphere at 514.5 nm With Aged Volcanic Aerosols




Figure 26. Backscatter Coefficients As A Function of Extinction Coefficients at 514.5 nm For A Midlatitude Summer Atmosphere With Aged Volcanic Aerosols




Figure 27. Comparison of Simulated and Inverted Data at 514.5 nm for Case 6 For Various Values of k for the (a.) Near-field and (b.) Far-field Solutions




Figure 28. Inverted Results at 514.5 nm with Variations in the Boundary Conditions Considered for Case 6 for the (a.) Near-field and (b.) Far-field Solutions




Figure 29. (a.) Backscatter and (b.) Extinction Coefficients As A Function of Altitude for a Midlatitude Summer Atmosphere at 514.5 nm With Fresh Volcanic *erosols

free background. The backscatter and extinction coefficients, as shown in Figure 30, are those in LOWTRAN 6 [Shettle, private communication, 1986].

Figures 31 (a.) and (b.) give the results from the inversions with different values of k and Figures 32 (a.) and (b.) give the results from the variation in the boundary conditions with k=1. As with the background stratospheric aerosol results (e.g. Figure 14), a power law with k=1 will reproduce the aerosol-free parts of the atmosphere but not those with aerosols present.

3.1.8 Case 2 Plus Combined Background Stratospheric and Fresh Volcanic Aerosols

Figures 33 (a.) and (b.) show the backscatter and extinction coefficients as a function of altitude for an atmosphere with 50 % background stratospheric and 50 % fresh volcanic aerosols added to an aerosol-free background. Figure 34 displays the backscatter and extinction coefficients.

Figures 35 (a.) and (b.) give the results from the inversions with different values of k and Figures 36 (a.) and (b.) give the results from the variation in the boundary conditions with k=1. Under these conditions, a power law with k=1 does a reasonable job of reproducing the simulated data.




Figure 30. Backscatter Coefficients As A Function of Extinction Coefficients at 514.5 nm For A Midlatitude Summer Atmosphere With Fresh Volcanic Aerosols




Figure 31. Comparison of Simulated and Inverted Data at 514.5 nm for Case 7 For Various Values of k for the (a.) Near-field and (b.) Far-field Solutions




Figure 32. Inverted Results at 514.5 nm with Variations in the Boundary Conditions Considered for Case 7 for the (a.) Near-field and (b.) Far-field Solutions

ASSESSMENT DESCRIPTION OF THE PROPERTY OF THE




Figure 33. (a.) Backscatter and (b.) Extinction Coefficients As A Function of Altitude for a Midlatitude Summer Atmosphere at 514.5 nm With 50 % Background Stratospheric and 50 % Fresh Volcanic Aerosols




Figure 34. Backscatter Coefficients As A Function of Extinction Coefficients at 514.5 nm For A Midlatitude Summer Atmosphere With Background and Fresh Volcanic Aerosols




Figure 35. Comparison of Simulated and Inverted Data at 514.5 nm for Case 8 For Various Values of k for the (a.) Near-field and (b.) Far-field Solutions




Figure 36. Inverted Results at 514.5 nm with Variations in the Boundary Conditions Considered for Case 8 for the (a.) Near-field and (b.) Far-field Solutions

3.2 Evaluating the Boundary Conditions in a "Real World" Situation

In the preceding sections, it was assumed that the boundary conditions were known. Then, it was shown that inaccuracies in the boundary conditions could have a significant impact on the inverted results. It is fair to ask the question, "Can the boundary conditions be known accurately?"

If one were using the far-field solution approach, the extinction coefficients at or near the surface would be required. If the visibility is known, the extinction coefficient at visible wavelengths can be evaluated from the Koschmieder formula

$$\sigma = 3.912 / V$$
 (13)

where V is the meteorological range. If the observer visi-ibility, $V_{\rm obs}$, is known, then V can be approximated as

$$V = (1.3 + / - 0.3) V_{obs}$$
 (14)

The observer visibility is not an exact measure of the transmission properties of the atmosphere and can vary greatly from one observer to another. Even with observer errors ignored, it is a quantity that can vary greatly during the day.

Over the ocean or uninhabited land areas, one would not have a way to calculate the extinction coefficient boundary conditions. Even if a surface extinction coefficient clima-

tology existed, it would still not be accurate enough for the inversion of lidar data.

For the near-field solution, the boundary condition represents the extinction at a high altitude, presumably in an altitude region well above any aerosol or cloud layers. In this case, the Rayleigh scattering values can be used for the boundary conditions. Assuming that the laser line was one in which little or no molecular absorption occured, the assumption would be valid. Seeing that the Rayleigh scattering is primarily dependent upon the wavelength (there is a minor dependence of pressure and temperature upon the atmospheric index of refraction), the near-field boundary conditions could be evaluated utilizing Rayleigh scattering coefficients. The net effect is that the near-field boundary conditions can be evaluated with an accuracy that can not be achieved for the far-field solution.

3.3 Summary of Results Utilizing A Power Law Inversion Approach

The calculations just presented have demonstrated that a power law inversion approach can accurately invert an atmosphere that only consists of Rayleigh scatters. The real atmosphere is rarely free of aerosols and, as demonstrated, a power law approach does not accurately invert the optical properties of a Rayleigh and non-Rayleigh atmosphere. To complicate matters, the atmosphere contains mixtures of different kinds of aerosols. Therefore, even if a power law could invert the optical properties for a given

aerosol, one would have to know in advance what kind of aerosol was being probed so as to select the correct value of k. This requirement coupled with the lack of a physical justification for the power law assumption forces one to conclude that a power law inversion approach cannot be used for the inversion of data from a spaceborne lidar system. An alternate approach can be recommended that is rooted in the physics of radiative transfer. The alternate approach will now be presented in the next chapter.

4. AN ALTERNATE INVERSION APPROACH FOR A SPACEBORNE LIDAR SYSTEM

Assuming that one can measure the atmospheric density profile, an expected profile of signal returns can be calculated (eg. Equation 1) for an atmosphere of pure Rayleigh scatterers, P_{Ray} . From this profile for a pure Rayleigh atmosphere, one can calcuate a profile of the ratio of the actual lidar returns to that expected from a Rayleigh atmosphere, R(r)

$$R(r) = \frac{P(r)}{\text{actual}}$$

$$R(r) = \frac{P(r)}{P(r)}$$
(15)

The atmospheric extinction profile consists of molecular and aerosols components,

$$\sigma(r) = \sigma(r)_{Ray} + \sigma(r)_{Aer}$$
 (16)

Expressing Eq (15) in its component terms gives

$$R(r) = \frac{\beta(r)}{\frac{BS,Ray}{BS,Aer}} + \frac{\beta(r)}{BS,Aer} \exp \left[-\int_{Aer}^{2\sigma} dr'\right]$$
(17)

where β bs, Aer and β bs, Ray are, respectively, the aerosol and Rayleigh backscatter coefficients.

The single scattering albedo, $\omega_{\rm O}$, can be given as the ratio of the total scattering to extinction coefficients

$$\omega_{O} = \beta_{S} / \sigma \tag{18}$$

The single scattering albedo can also be given in terms of the phase function, $p(\Omega)$,

$$\omega_{O} = \frac{1}{4\pi} \int p(\Omega) d\Omega \qquad (19)$$

Substituting Equation (18) into Equation (17) gives

STATES STATES STATES

$$R(r) = \frac{\beta(r)_{BS,Ray} + \beta(r)_{S,Aer} p(180)}{\beta(r)_{Ray}} exp\left[-2\int \beta_{S} dr'/\omega_{o}\right]$$
(20)

Equation 20 can be solved numerically with an iterative method, such as the Newton-Raphson technique²², to solve for the total scattering coefficient.

A sample inversion using this alternate technique is given in Figure 37. The sample calculations were made using the aged volcano parameters of Case 6. The calcuations assumed a constant single scattering albedo of 0.9519. inversion result is quite good, with a maximum difference between the actual profile of about 8 %. Figures 38 (a). and (b.) show, respectively, the impact of variations in the single scattering albedo and fraction of scattering into the backwards direction. In both cases, the values were perturbed by + and - 10 %. The results for this indicated that the inversion was somewhat less sensitive to variations in the single scattering albedo. A full set of sensitivity calculations should be performed utilizing other assumed aerosol models before any general conclusions can be made concerning what are the most sensitive parameters in this alternate inversion technique. For example, one must have the profile of Rayleigh scattering extinction

Dahlquist, G. and A. Bjorck (1974) <u>Numerical Methods</u>, Prentice-Hall, Inc., Englewood Cliffs, New Jersey, 222-227.




Figure 37. Inverted Results at 514.5 nm with the Alternate Inversion Techniques for a Simulated Atmosphere with Aged Aerosols




Figure 38. Inverted Results at 514.5 nm with Variations in (a.) the Single Scattering Albedo and (b.) the Fraction of Backscattered Radiation

coefficients and to do this one must know the atmospheric density profile. Also, one must have some information about the single scattering albedo and the fraction of backscattered radiation. One can obtain these either from the literature or from detailed sets of Mie calculations. In order to utilize that information, one must be willing to limit the range of possible values by assuming some knowledge about the aerosol layer. For example, one could say that if the returns are from a specific altitude region they must be from a certain type of aerosol. Also, using the latitude and longitude of the satellite track one could say whether or not the returns are from an urban or rural type of aerosol. The point to stress is that the alternate technique still requires some knowledge of the aerosol, primarily a guess of what type of aerosol is causing the return.

5. SUMMARY OF INVERSION TECHNIQUES AND RECOMMENDATIONS FOR FUTURE WORK

5.1 Summary of Results

An examination of inversion techniques applicable for a spaceborne lidar system has been performed. The purpose of the examination has been to recommend a technique that could be used with the lidar system under development by AFGL.

In a purely Rayleigh atmosphere with no or minimal gaseous absorption, a power law relationship between back-scattering and extinction exists in which k=1. In an atmosphere with aerosols and clouds, the assumption of a power law relationship is tenuous at best. Although popular with researchers, the examination of the literature leads us to conclude that the power law relationship has no physical basis to support its extensive use. For any application probing different regions of the atmosphere and different types of aerosols, one cannot assume a single set of power law parameters for the entire atmosphere.

An alternate inversion approach has been presented based on the fundamental radiative transfer characteristics of the atmosphere. The approach is rooted in fundamental physics but, still, does not eliminate the problem of more unknowns than equations. For the approach to be used, one must still make an assumption about the type of aerosol responsible for the lidar signal.

5.2 Recommendations for Future Research

The alternate inversion approach that has been presented should be researched further to investigate its sensitivity to variations in the input parameters. This sensitivity study would help to establish the accuracy requirements of the input data.

The alternate inversion approach requires information on the phase function and the single scattering albedo of the aerosols. A review of the literature should be performed to determine what measurement database exists for the type of aerosols that would most likely be encountered by a spaceborne lidar system. Where measurements are lacking, calculations should be performed or results from previous calculations assembled.

Finally, the alternate inversion technique should be tested against the lidar data obtained from the recent test flight. This would help to establish the usefulness of the technique in the "real world" rather than the highly unrealistic situation in which the actual profiles are known.

References

- 1. Murray, E. R., M. F. Williams and J. E. van der Laan (1978) Single-ended Measurement of Infrared Extinction Using Lidar, Applied Optics, 17:296.
- 2. Collis, R. T. H. (1966) Lidar: A New Atmospheric Probe, Q. J. R. Meteorol. Soc. 92:220.
- 3. Viezee, W., E. E. Uthe and R. T. H. Collis (1969) Lidar Observations of Airfield Approach Conditions: An Exploratory Study, J. Appl. Meteorol. 8:274.
- 4. Kohl, R. H. (1978) Discussion of the Interpretation Problem Encountered in Single-Wavelength Lidar Transmissometers, J. Appl. Meteor., 17:1034.
- 5. Brown, Jr., R. T. (1979) Comments on "Discussion of the Interpretation Problem Encountered in Single-Wavelength Lidar Transmissometers, J. Appl. Meteor., 18:711.
- 6. Kohl, R. H. (1979) Reply, J. Appl. Meteor., 18:712.
- 7. Klett, J. D. (1981) Stable Analytical Inversion Solution for Processing Lidar Returns, Applied Optics 20:211.
- 8. Klett, J. D. (1985) Lidar Inversion with Variable Back-scatter/Extinction Ratios, Applied Optics 24:1638.
- 9. Hughes, H. G., J. A. Ferguson and D. H. Stephens (1985)
 Sensitivity of a Lidar Inversion Algorithm to
 Parameters Relating Atmospheric Backscatter and
 Extinction, Applied Optics, 24:1609.
- 10. Bissonnette, L. R. (1986) Sensitivity Analysis of Lidar Inversion Algorithms, Applied Optics, 25:2122.
- 11. Ferguson, J. A. and D. H. Stephens (1983) Algorithm For Inverting Lidar Returns, Applied Optics, 22:3673.
- 12. Mulders, J. M. (1984) Algorithm for Inverting Lidar Returns: Comment, Applied Optics, 23:2855.
- 13. Curcio, J. A. and G. L. Knestrick (1958) Correlation of Atmospheric Transmission and Backscattering, J. Opt. Sci. Am., 48:686.
- 14. Twomey, S. and H. B. Howell (1965) The Relative Merit of White and Monochromatic Light for the Determination of Visibility by Backscattering Measurements, Applied Optics, 4:501.

- 15. Fenn, R. W. (1966) Correlation Between Atmospheric Back-scattering and Meteorological Range, <u>Applied Optics</u>, <u>5</u>:293.
- 16. Pinnick, R. G., S. G. Jennings, P. Chylek, C. Ham and W. T. Grandy, Jr. (1983) Backscatter and Extinction in Water Clouds, J. Geophys. Res., 88:6787.
- 17. Shettle, E. P. (1985) Backscattering by Atmospheric Aerosols, Presented at the IAMPA/IAPSO Joint Assembly, Honolulu, Hawaii, 5-16 August 1985.
- 18. Evans, B. T. N. (1986) Sensitivity of the Lidar Ratio to Changes in Size Distribution and Index of Refraction,

 Thirteenth International Laser Radar Conference, NASA Conference Publication 2431, National Aeronautics and Space Administration, Code NIT-4, Washington, D. C.
- 19. DeLuisi, J. J., Schuster, B. G. and Sato (1975)
 Separation of Dust and Molecular Scattering
 Contributions to the Lidar Observation: A Method,
 Applied Optics 14:1917.
- 20. Kastner, M. and H. Quenzel (1986) The Usefulness of Klett's Inversion Algorithms to Simulated Satellite Lidar Returns, Thirteenth International Laser Radar Conference, NASA Conference Publication 2431, National Aeronautics and Space Administration, Code NIT-4, Washington, D. C.
- 21. McClatchey, R. A., R. W. Fenn, J. E. A. Selby, F. E. Volz and J. S. Garing (1972) Optical Properties of the Atmosphere, Air Force Cambridge Research Laboratories, Hanscom Field, Bedford, Massachusetts, AFCRL-72-0497, AD753075.
- 22. Dahlquist, G. and A. Björck (1974) <u>Numerical Methods</u>, Prentice-Hall, Inc., Englewood Cliffs, New Jersey, 222-227.

ACCOUNT RECORDED INTEREST INTRODUCED CONTROL C